



1975 Scirocco

1975 Scirocco

Scirocco.

Styled by Giugiaro of Italy. To be contemporary.
Engineered by Volkswagen. To take performance seriously.

- 4 cylinder, water-cooled, overhead cam, transverse mounted engine. Up front.
- Front wheel drive.
- Front disc brakes, power assisted.
- 4-speed, fully synchronized, transverse mounted transmission. Or optional 3-speed automatic.
- 4-wheel, independent suspension.
- Negative steering roll radius.
- Independent, rear stabilizer axle.
- Lightweight, aluminum-magnesium alloy rims.
- Rack and pinion steering.
- Steel belted radial tires.

Scirocco.

A commitment to the future. When it's needed most.

Now. From Volkswagen.

SPECIFICATIONS

| | | VW SCIROCCO |
|----------------------------------|---|--|
| ENGINE: | Type | Water-cooled, transverse-front mount, overhead cam |
| | No. cylinders | 4 cyl. in-line |
| | Bore | 76.5 mm. (3.01 in.) |
| | Stroke | 80.0 mm. (3.15 in.) |
| | Displacement | 1471 cc. (89.75 cu. in.) |
| | SAE Net H.P. | 70/6000 rpm. |
| | Max. Torque, SAE Net | 81/3500 rpm. |
| | Compression Ratio | 8.2:1 |
| | Carburetion | Two-stage downdraft carburetor, automatic choke. |
| | TRANSMISSION & DIFFERENTIAL: | Type |
| No. Speeds | | 4 forward, 1 reverse. |
| Final drive | | Front wheel drive, double jointed axles. |
| Clutch | | Single disc, dry. |
| CHASSIS & SUSPENSION: | Frame | Unitized body with energy absorbing front and rear sections. Bolt-on front fenders. |
| | Suspension-Front | Independent, coil/shock absorber struts with lower triangular control arms. Negative steering roll radius. |
| | Suspension-Rear | Coil/shock absorber struts. Independent stabilizer axle. |
| | Service Brake | Dual diagonal, power assisted. Discs front w/single piston floating caliper. |
| | Parking Brake | Cable operated, rear. |
| | Rim Size | 5J x 13 |
| | Tire Size | Radial ply, steel belted, 175/70 SR 13 |
| ELECTRICAL SYSTEM: | Steering | Rack and pinion |
| | Rated Voltage | 12V/55 A. Alternator |
| | Battery | 12V 54 AMP/h |
| | Ignition | Battery, coil, distributor |
| DIMENSIONS: | Wheelbase | 94.5 in. |
| | Track, front | 54.7 in. |
| | Track, rear | 53.1 in. |
| | Length | 155.7 in. |
| | Width | 64.0 in. |
| | Height | 51.5 in. |
| | Ground Clearance | 5.3 in. |
| | Turning Circle | 32.2 ft. (approx.) |
| WEIGHTS: | Dry Weight | 1874 lbs. |
| | (automatic) | 1929 lbs. |
| | Payload | 838 lbs. |
| | (automatic) | 783 lbs. |
| PERFORMANCE: | Top Speed | 104 mph. |
| | (automatic) | 101 mph. |
| | Fuel Consumption DIN 70030 | 29 mpg. |
| | (automatic) | 27 mpg. |
| | Acceleration | 0-60 10.3 sec. |
| | (automatic) | 0-60 11.8 sec. |